# KANTHAL

# CUPROTHAL® SAFETY INFORMATION SHEET

数据表

This Safety Information Sheet provides essential health, safety, and environmental information for Cuprothal®, a copper-nickel (CuNi) alloy primarily used in electrical resistance and heating applications. The information herein is intended to assist users in the safe handling, storage, processing, and disposal of Cuprothal® in various industrial and manufacturing applications. While Cuprothal® is considered stable under normal conditions, appropriate precautions should always be taken to minimize risks during its use. This document is not a substitute for regulatory compliance or a Material Datasheet, but complements it by offering additional safety guidance specific to this material.

# IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Trade name: Cuprothal® 5, 10, 15, 30, 49, 49TC, CuNi67, SX, WX, JN, Manganina 43

Product type: Resistance Heating Alloy, Thermo Alloy

Manufacturer/Supplier: Kanthal AB Box 502 734 27 Hallstahammar +46 220-210 00

E-mail: ehs@kanthal.com

Emergency telephone: User your local emergency number

#### HAZARDS IDENTIFICATION

H-value:

H351 Suspected of causing cancer.

H317 May cause an allergic skin reaction.

H372 Causes damage to organs through prolonged or repeated exposure.

Injurious to health properties:

Nickel limited evidence of a carcinogenic effect.

Nickel may cause sensitization by skin contact.

Cobalt may cause sensitization by inhalation and skin contact

# COMPOSITION/INFORMATION ON INGREDIENTS

	1
$\alpha$	1
αV:C1	۲
`	١.
$\mathcal{C}$	V
_	_
_	_
a	J
ac.	V
_!	L
(1	J
	J
_	_
Ž,	כ
75-7	7
7257	242
2025-6	7070
2025-03-	7070
1 2025_C	4040
	7070
	7070
	7070
	7070

Compounds*	EINECS-no.	CAS-no.	Content %	H-value
Nickel	231-111-4	7440-02-0	2-68	H351
				H317
				H372
Copper	231-159-6	7440-50-8	Balance	
Iron	231-096-4	7439-89-6	Max 3	
Manganese	231-105-1	7439-96-5	Max 12,5	

<sup>\*</sup> Other elements may be present, such as Co. These are not classified as hazardous, or are below the concentration levels for classification of these alloys as hazardous, and are not subject to recognized occupational exposure limits.

#### FIRST AID MEASURES

Inhalation: Move to fresh air.

Skin contact: Wash with soap and water.

Eye contact: Rinse immediately with water for several minutes, with eyelids held open.

Ingestion: Not a normal route of exposure.

# FIRE-FIGHTING MEASURES

Suitable extinguishing media: Use suitable extinguishing media for surrounding materials and type of fire.

Extinguishing media which shall not be used for safety reasons: None known.

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases: None known.

Special protective equipment for firefighters: Wear fully protective impervious suit.

# ACCIDENTAL RELEASE MEASURES

Personal precautions: Use protective clothing and gloves. Also see p.8

Environmental precautions: -

Methods for cleaning up: -

### HANDLING STORAGE

 $Handling: Follow\ generally\ accepted\ industrial\ practice\ for\ good\ hygiene.$ 

Storage: Keep dry.

#### **EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Exposure limit values

Hygiene standards and exposure limits may differ from country to country. Check those currently applying in your country and comply with regulations. Examples of exposure limit applying Sweden are given below:

Compound Exposure limit Type of value

	1
⋷	1
▭	1
⊨	
⊨	
⊨	
⊨	
⊨	
누	
_	J
$\alpha$	٦
$\simeq$	_
``	Į.
Ċ	j
_	_
`	
M	٦
$\tilde{\sim}$	
١.	٧
×	
۲.	2
	J
. !	L
Ц	J
(,	J
۲	7
5	7
200	1
200	7
10.48 FILES 10.48 FILES 10.48	7
	404
	7
	707

Nickel	0,5 mg/m3	NGV (Total)	
Copper	0,2 mg/m3	NGV (Respirable)	
	1 mg/m3	NGV (Total)	
Manganese	0,1 mg/m3	NGV (Total)	
	0,2 mg/m3	NGV (Respirable)	
Cobalt	0,2 mg/m3	NGV (Total)	
	0,05 mg/m3	NGV (Total)	

NGV= Level Limit Value, sanitary limit value for exposure during one working day.

Exposure controls

Preventive action: Good general ventilation is recommended.

Respiratory protection: Use when necessary.

Hand protection: Protective gloves, avoid skin contact.

Eye protection: Wear safety glasses when tooling.

Skin protection: Wear suitable protective clothing and protective shoes.

#### PHYSICAL AND CHEMICAL PROPERTIES

Form: Solid, metal

Colour: Metallic

Odour: Odourless

Density: ~8,9g/cm3

Melting point (approx): ~1,090 - 1,300°C (~1,990-2,370°F)

Water solubility: Insoluble

# STABILITY AND REACTIVITY

Conditions to avoid: -

Materials to avoid: -

Hazardous decomposition products: -

# TOXICOLOGICAL INFORMATION

 $Inhalation: \ Dust \ may \ cause \ sensitive \ persons \ problem \ with \ respiration.$ 

Skin contact: May cause contact eczema and allergy when repeatedly skin contact.

Eye contact: Product dust may cause temporary mechanical eye irritation.

Ingestion: Not a normal route of exposure.

# Nickel

Nickel is the most commonly occurring contact allergen. According to surveys from the USA, Italy, Denmark,

Finland and Sweden, 8-22 % of women and 0.3-3 % of men develop hypersensitivity to nickel (National Chemicals Inspectorate, Sweden, 1995). The main method of exposure is contact with metallic nickel and/or nickel alloys.

Exposure to nickel has been linked to a risk of lung cancer and nasal cancer, but it has not been possible to identify the form in which nickel is carcinogenic.

#### **ECOLOGICAL INFORMATION**

No data available.

#### **DISPOSAL CONSIDERATIONS**

Disposal in accordance with all applicable local and national regulations.

#### TRANSPORT INFORMATION

Road transport (ADR): Not classified as dangerous in the meaning of transport regulations.

# **REGULATORY INFORMATION**

H-value:

H351 Suspected of causing cancer.

H317 May cause an allergic skin reaction.

H372 Causes damage to organs through prolonged or repeated exposure.

P-value:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P314 Get medical advice/ attention if you feel unwell.

#### OTHER INFORMATION

Information in this Safety Information Sheet is based on the form the product is released on the market.

List of relevant H phrases:

H351 Warning; Suspected of causing cancer.

H317 Warning; May cause an allergic skin reaction.

H372 Danger; Causes damage to organs through prolonged or repeated exposure.

# Declaration

The information given in this safety information sheet is based on the present level of our knowledge and experience. The data sheet describes the products with respect to safety requirements. The data given is not intended as a confirmation of product properties and does not constitute a legal contractual relationship, nor should it be used as the basis for ordering these products.

Revision:

Revised in accordance with CLP regulation. EC 1272/2008.

